



SÚNG HƠI CÓ BÁNH CỐC 3/8"

SI-1320A

SI-1261/1261S 3/8" Ratchet Wrench

- Maximum Torque: 110Nm
- Japan and foreign patent(s) pending as the "Slide Switch" for the reverse function
- Plastic covered regular size body
- The lightest 960g in this class
- Lightweight and high strength super duralumin is used for housing



SI-1320A 3/8" Ratchet Wrench

- Maximum Torque: 80Nm
- Standard ratchet wrench with the front exhaust 3/8"sq. anvil
- Reasonable price



Model Number	Shank Size in./ (mm)	Maximum Torque Nm/ (ft-lb)	Working Torque Range Nm/ (ft-lb)	Bolt Cap mm/ (in.)	Free Speed rpm	Weight kg/ (lb)	Over Length mm/ (in.)	Noise Level dBA/ (power)	Vibration m/s ²	Avg. Air Consumption CFM	Air Inlet Size in.	Hose Size mm/ (in.)
SI-1208	3/8 / (9.5)	40/(30)	0-30/(0-22)	10/(3/8)	200	0.54/(1.20)	170/(6.69)	86/(99)	3.5	2.2	1/4	10/(3/8)
SI-1252	3/8 / (9.5)	47/(35)	0-35/(0-26)	10/(3/8)	260	0.56/(1.24)	168/(6.61)	79/(92)	3.5	2.4	1/4	10/(3/8)
SI-1261/ SI-1261S	3/8 / (9.5)	110/(81)	0-65/(0-48)	10/(3/8)	170	1.20/(2.65)/ 0.96/(2.12)	259/(10.2)	84/(97)	7.0	3.0	1/4	10/(3/8)
SI-1320A	3/8 / (9.5)	80/(59)	0-60/(0-44)	12/(1/2)	160	1.16/(2.57)	265/(10.4)	93/(105)	7.6	2.7	1/4	10/(3/8)
SI-1340B	3/8 / (9.5)	110/(81)	0-85/(0-63)	12/(1/2)	160	1.14/(2.50)	265/(10.4)	89/(102)	7.6	2.5	1/4	10/(3/8)
SI-1208Q	3/8 / (9.5)	40/(30)	0-30/(0-22)	10/(3/8)	240	0.53/(1.17)	170/(6.69)	84/(87)	3.5	2.3	1/4	10/(3/8)